

Mini IR Thermometer with Type K input

Adjustable High/Low setpoints with audible alarm and 0.1° resolution

Features:

- Wide range (-76 to 932°F) non-contact IR thermometer
- Adjustable emissivity increases measurement accuracy for different surfaces
- Adjustable High/Low setpoints with audible alarm alerts user when temperature exceeds programmed setpoints
- Built-in laser pointer improves aim
- Auto-hold after releasing the Measure button
- Type K thermocouple input
- Min/Max/Avg plus differential between Max – Min
- Data Hold, Auto power off with disable function, low battery indication
- Complete with 2 AAA batteries (Carrying case and Type K thermocouple sold separately)

Applications:

- Measure surface temperature of objects difficult to reach or unsafe to contact
- Measure hot spots in electrical panels and equipment
- In-process temperature measurements



CE

Specifications	
Display Counts:	2000 count Backlit LCD
Range:	-76 to 932°F (Infrared); -83 to 1999°F (Type K) -60 to 500°C (Infrared); -64 to 1400°C (Type K)
Basic Accuracy:	InfraRed $\pm(2\% \text{ rdg})$ or $\pm 4^\circ\text{F}/\pm 2^\circ\text{C}$ (whichever is greater) Type K $\pm(1\% \text{ rdg})$ or $\pm 1.8^\circ\text{F}/\pm 1^\circ\text{C}$ (whichever is greater)
Max Resolution:	0.1°F/°C
Emissivity:	0.1 to 1.00 Adjustable
Field of view:	11:1
Dimensions:	6.9x1.5x2.8" (175x39x72mm)
Weight:	6.3oz (179g)

Ordering Information:

- 42535**.....Mini IR Thermometer with Type K Input
42535-NIST...Mini IR Thermometer with Type K Input with NIST certificate
872501-S.....Type K Bead Wire Temp Probe (-4 to 482°F/-20 to 250°C)



Make mine an Extech!
www.extech.com

10/13/04 - R1