

## AC Line Splitter Model ALS-1

For use with clamp-on meters & multimeters using current probes



### ► FEATURES

- Avoids splitting lines - makes reading current easy
- Increases sensitivity of clamp-on current probes and clamp-on meters ten times in X10 mode
- Direct reading X1 mode
- Voltmeter input jacks
- Integral ground conductor
- Facilitates reading current draw of device plugged into it
- Facilitates reading current draw through extension cords
- 120V, 15A capacity

## Non-Contact AC Voltage Detector Model NC-1



### ► SPECIFICATIONS

MODEL	NC-1
<b>Voltage Sensitivity</b>	120 to 240Vac
<b>Frequency</b>	50/60Hz
<b>Detection Distance</b>	<5mm
<b>Over Voltage</b>	600V CAT III
<b>Battery</b>	2 x 1.5V AAA Alkaline (included)
<b>Safety</b>	For indoor use and in accordance with over voltage 600V CAT III, Pollution Degree 2

## Model 275HVD

Warns the operator of live conductors with the use of its detection sensor

### ► SPECIFICATIONS

MODEL	275HVD
<b>ELECTRICAL</b>	
<b>Detection Frequency</b>	45 to 70Hz
<b>Ranges</b>	240V, 2kV, 6kV, 11kV, 22kV, 33kV, 132kV, 275kV
<b>Detection</b>	Selection range is detected at approximately 10" (25cm) from the voltage. Greater detection distances can be obtained at lower voltage positions
<b>Power Source</b>	Three 1.5V C cell batteries (included)
<b>MECHANICAL</b>	
<b>Self Test</b>	User selectable
<b>Indicators</b>	Bright red LED and audible buzzer
<b>ENVIRONMENTAL</b>	
<b>Operating Temperature</b>	5° to 130°F (-15° to 55°C)
<b>Storage Temperature</b>	-4° to 150°F (-20° to 65°C)
<b>Humidity</b>	0 to 93% RH @ 104°F (40°C)

Note: Not designed to work on shielded cable or enclosure.



### ► FEATURES

- Non-contact high voltage detector
- Wide range of detection; 80V to 275kV; one instrument fits all applications
- Eight switch-selectable voltage sensitivity ranges
- Lightweight, minimizes sway at the end of long hot sticks
- Audible and visual (LED) indication of live voltage
- Self-test ensures that all system functions and indicators are working properly by energizing the complete system
- Designed for use with hot sticks incorporating a shotgun adapter



### ► PRODUCT INCLUDES

Hard carrying case, three C cell batteries, shotgun adapter and user manual.

CATALOG NO.	DESCRIPTION
2121.05	AC Line Splitter Model ALS-1
2121.09	Non-Contact AC Voltage Detector Model NC-1
2131.12	Non-Contact High Voltage Detector Model 275HVD (240V to 275kV) Manual self-test