

Fast Response Oxygen Analyzer



FEATURES	BENEFITS
Advanced Solid State Sensor	Provides High Precision Oxygen Measurements
Measures PPB to 100%	One Instrument Does It All
Response in Milliseconds	Provides Exceptional Tracking of Process Conditions.
Non-depleting Sensor	Designed to Provide Years of Operation
User Scalable Analog Outputs	Better Defines the Concentration Range of Interest
Dual User Adjustable Alarms	Set Critical Process Limits
Microprocessor Controller	Helps to Ensure Dependable and Accurate Reading
Built-in Sample By-Pass gas	Helps to promote rapid transport of the sample gas

Product Description

The Series ZrO2000 Fast Response Oxygen Analyzer is a microprocessor based instrument designed to measure gas phase oxygen concentrations over a range of 0-100%. The non-depleting sensor used in the Series ZrO2000 Fast Response Oxygen Analyzer is a zirconium type that exhibits fast response times. The analyzer is housed in a NEMA 1 enclosure rated for general purpose use. The front panel contains five switches that provide access to the analyzer's settings. Oxygen values are displayed on a 0.7" (17.8 mm) high 6 digit liquid crystal display (LCD). The instrument is equipped with two oxygen alarm relays. Both relays are Form C (SPDT) types rated at 10 amps at 115/230 VAC/ 30 VDC and are user configurable for fail-safe operation. In addition to the alarm relays, the Series ZrO2000 Fast Response Oxygen Analyzer has a built-in audible alarm and red LEDs for visual indication of an oxygen alarm condition. There are also two green LEDs to indicate whether the LCD is displaying parts per million (PPM) or percent (%).

The audible alarm may be manually canceled at anytime. If the audible alarm is canceled and the alarm event continues, indications of this condition will still be available through the front panel LEDs and relay contact(s). Two flow meters are standard equipment for the Series ZrO2000 Fast Response Oxygen Analyzer, one for the "Sample Flow" and another for the "Bypass Flow".

The Series ZrO2000 Fast Response Oxygen Analyzer comes equipped with two standard analog outputs. These can be configured for 0-20 mADC or 4-20 mADC separately. Both are scalable by the user. The analyzer accepts a universal input of 90VAC to 264VAC @ 50-60Hz. The Series ZrO2000 Fast Response Oxygen Analyzer incorporates standard features that make it suitable for many applications. However, for certain requirements, the user may desire to augment the capabilities of the instrument by equipping it with a sample pump or pressure regulator.

Specifications PERFORMANCE

Measurement Ranges: 0% to 100%

Accuracy: Percent: $\pm 2\%$ of reading or 0.05% absolute whichever is greater.

Trace: $\pm 2\%$ of reading or ± 0.5 ppm absolute whichever is greater.

NOTE: The sample gas used with the ZRO2000 must not contain any hydrocarbon vapors, hydrogen, carbon monoxide, or other reducing gases. Sample tubing should be cleaned for oxygen service. Please consult the factory for additional information.

Response Time: < 5 seconds at 0.15 liters per minute (LPM) over 1 decade.

The response time for measurements of less than 50 PPM or less depend to a great extent on the design of the sample delivery system including the materials used.

Sensor Type: Zirconium Oxide

Operating Temperature of Analyzer: 50° to 104°F (10° to 40°C)

Warranty: Two Years Electronics
One Year Sensor

ELECTRICAL

Display: 0.7" (17.8 mm) high 6 digit liquid crystal display

Resolution: 0.01 on highest reading & 0.001 ppm on lowest reading

Input Power: Universal 90-264 VAC, 50 or 60 Hz

Standard Outputs: (2) Selectable 0-20 mA DC or 4-20 mA DC, both scalable by user

Oxygen Alarm Relays: Two (2) SPDT Form C contacts rated 10 A @ 30 V DC /115/230 VAC.

Alarms may be cleared manually or automatically, by user selection.

Audible Alarm: Internal audible alarm

Audible Alarm: Cancel Front panel switch

SAMPLE GAS CHARACTERISTICS

Maximum Sample Temperature: 122°F (50°C)

Maximum Sample Pressure: (PSIG) (0.007 to 0.035 kg/cm²)

Sample Gas Moisture Limits: 85% RH

CONSTRUCTION

Enclosure: Aluminum, rated NEMA 1.

Enclosure Dimensions: 13 inches (330 mm) - length
10.71 inches (272 mm) - width
6.3 inches (160 mm) - height

Note: All dimensions are without optional equipment

Gas Connections: 1/4" stainless steel compression fittings.

Weight: (Bench top Configuration)
9.4 pounds (4.26 kg.) / 10.4 pounds (4.72 kg.)
with optional sample pump.

Alpha Omega Instruments Corp. reserves the right to change or modify its product specifications without notice

Applications

Modified Atmosphere Packages (MAP)	Glove Boxes
Biological Reactors	Critical Welding
Pharmaceutical Processing	Heat Treating
Semiconductor Manufacturing	Leak Detection
Vessel Blanketing	Air Separation

Optional Equipment

Pressure Regulators	Sample Pumps
---------------------	--------------

AO ALPHA OMEGA
INSTRUMENTS

40 Albion Road, Suite 100, Lincoln, RI 02865
Tel: 401.333.8580, 800.262.5977 Fax: 401.333.5550
Email: salescontact@aoi-corp.com Web: aoi-corp.com

Alpha Omega Instruments Accepts VISA, Mastercard, and AMEX