

Waterproof ExStik® II Dissolved Oxygen Meter

Easy to replace screw on membrane cap with optional extension cables

Features:

- Oxygen level displayed as % Saturation from 0 to 200.0% or Concentration from 0 to 20.00ppm (mg/L)
- Adjustable Altitude Compensation (0-20,000ft in 1,000ft increments)
- Adjustable Salinity Compensation from 0 to 50ppt
- Analog bargraph indicates trends
- Memory stores up to 25 data sets with DO and Temperature reading
- Self calibration on power up
- Data Hold, Auto power off, Low battery indicator
- Waterproof to IP57
- Optional 3 ft (1m) or 16ft (5m) extension cable with probe weight.
- Complete with DO electrode, protective sensor cap, spare membrane cap, electrolyte, four 3V CR-2032 batteries, and 48" (1.2m) neckstrap.



Specifications:	Range	Max Resolution	Basic Accuracy
DO (saturation mode)	0 to 200.0%	0.1%	±2% FS
DO (concentration mode)	0 to 20.00ppm (mg/L)	0.01ppm (mg/L)	0.4ppm (mg/L)
Temperature:	32 to 122°F (0 to 50°C)	0.1°F/°C	±1.8°F (1°C)
Dimensions	1.4x 6.9x1.6" (36 x176 x 41mm)		
Weight:	3.8oz (110g)		



DO603 Membrane Kit includes 6 screw on membrane caps, 15mL filling solution and polishing paper



Choice of optional 3ft (1m) or 16ft (5m) extension cable with probe weight



Extension cable attached to meter



Bonded membrane cap for easy replacement



Available Q1 2005

Ordering Information:

- DO600**ExStik® II Dissolved Oxygen Meter
DO610ExStik® II DO/pH/Conductivity Kit
DO603Membrane Kit for DO600 and DO605
DO605Spare ExStik® II Dissolved Oxygen Electrode module
EX010Extension Cable, 3ft (1 Meter) with probe weight for ExStik
EX050Extension Cable, 16ft (5 Meter) with probe weight for ExStik
CA895Carrying case, Small with Belt Loop
CA903Carrying case for ExStik™ kit

EXTECH INSTRUMENTS CORPORATION
285 Bear Hill Road, Waltham, MA 02451-1064, U.S.A.
Phone: 781-890-7440 • FAX 781-890-7864

ISO 9001:2000 CERTIFIED

"Make mine an Extech!"™
www.extech.com



02/16/06 - R5