


Welding adapter for process sensors

WELDING ADAPT D85 G1 V4A 3A

recommended for wall thickness <= 4 mm. There are more suitable welding adapters for thicker walls.



1 G1 internal thread Aseptoflex Vario
2 Leakage port
3 sealing area



Application

Design	with leakage port	
Installation	recommended for wall thickness <= 4 mm	
Pressure rating	16 bar	1.6 MPa
Note on pressure rating	for the connection sensor - adapter	

Tests / approvals

Pressure Equipment Directive	A possible classification to PED depends on the application and has to be carried out by the user / operator.
Safety instructions	The compatibility between medium and product material has to be checked in all applications.

Mechanical data

Weight	[g]	762.6
Materials (wetted parts)		stainless steel (316L/1.4435) surface characteristics: Ra < 0,4 µm / Rz = 4 µm
Sensor connection		G 1 internal thread Aseptoflex Vario
Process connection		welding adapter Ø 85 mm
Sealing		Gasket

Accessories

Items supplied	O-rings: 1 x (24 x 2 mm), EPDM, E30054
Accessories (optional)	O-ring: 1 x 24 x 2, FKM, FDA compliant, E30123
	Welding mandrel, E30452
	welding mandrel, water-cooled, E30532
	leak test, E30530
	grinding protection, E30160

Remarks

Notes	recommended for wall thickness <= 4 mm. There are more suitable welding adapters for thicker walls.
Pack quantity	1 pcs.