

ExStik® II Conductivity Kit

Waterproof meter incorporates a highly accurate multi-ranging sensor that measures four parameters – Conductivity, TDS, Salinity, and Temperature

Features:

- Convenient Conductivity Kit with all the calibration standards, sample plastic cups and carrying case included for easy travel
- Autoranging meter offers 3 ranges with 8 units of measure including $\mu\text{S}/\text{cm}$, mS/cm , ppm, ppt, mg/L , g/L , $^{\circ}\text{F}$, and $^{\circ}\text{C}$
- Simultaneous display of Conductivity or TDS plus Temperature and bargraph
- Memory stores up to 15 labeled readings
- Adjustable Conductivity to TDS ratio factor from 0.4 to 1.0
- Self calibration on power up
- Waterproof to IP57
- Large 3-1/2 digit (2000 count) Digital display with analog bargraph to indicate sample trends
- Data Hold, Auto Power Off and low battery indication
- Automatic Temperature Compensation of 2% per $^{\circ}\text{C}$
- Auto standard recognition for calibration (84 $\mu\text{S}/\text{cm}$, 1413 $\mu\text{S}/\text{cm}$, and 12880 $\mu\text{S}/\text{cm}$)
- Easy to replace Conductivity cell module
- Plastic sample cup and iron cast weighted base allows for hands-free operation while holding up the meter during measurement stage
- EC410 kit includes EC400 ExStik® Conductivity/TDS/ Salinity Temperature Meter, with sensor, protective cap, 84 $\mu\text{S}/\text{cm}$, 1413 $\mu\text{S}/\text{cm}$ and 12880 $\mu\text{S}/\text{cm}$ calibration standards (30mL bottle each), weighted base, 3 sample plastic cups with caps, four 3V CR-2032 batteries, 48" (1.2m) neckstrap, and carrying case



Specifications	Ranges	Max. Resolution	Basic Accuracy
Conductivity:	0 to 199.9 $\mu\text{S}/\text{cm}$	0.1 $\mu\text{S}/\text{cm}$	$\pm 2\%$ FS
	200 to 1999 $\mu\text{S}/\text{cm}$	1 $\mu\text{S}/\text{cm}$	
	2.00 to 19.99 mS/cm	0.01 mS/cm	
TDS:	0 to 99.9ppm (mg/L)	0.1ppm (mg/L)	$\pm 2\%$ FS
	100 to 999ppm (mg/L)	1ppm (mg/L)	
	1.00 to 9.99ppt (g/L)	0.01ppt (g/L)	
Salinity:	0 to 99.9ppm (mg/L)	0.1ppm (mg/L)	$\pm 2\%$ FS
	100 to 999ppm (mg/L)	1ppm (mg/L)	
	1.00 to 9.99ppt (g/L)	0.01ppt (g/L)	
Temperature:	32° to 149°F (0° to 65°C)	0.1°	$\pm 1.8^{\circ}\text{F}/1^{\circ}\text{C}$
Power:	Four SR44W button batteries		
Dimensions:	Meter: 1.4x6.8x1.6" (36x173x41mm)		
	Kit: 9.5x6.8x2.8" (241x173x71mm)		
Weight:	Meter: 3.8 oz (110g)		
	Kit: 1.56 lbs (708g)		

Ordering Information:

- EC410** ExStik® Conductivity/TDS/Salinity Kit
- EC400** ExStik® Conductivity/TDS/Salinity Meter
- EC405** Spare Conductivity Cell
- EC-84-P** 84 $\mu\text{S}/\text{cm}$ Conductivity Standard (30mL)
- EC-1413-P** 1413 $\mu\text{S}/\text{cm}$ Conductivity Standard (30mL)
- EC-12880-P** 12,880 $\mu\text{S}/\text{cm}$ Conductivity Standard (30mL)
- EX007** Spare sample solution cups (24pk)
- EX010** Extension Cable, 3ft (1 Meter) with probe weight for ExStik
- EX050** Extension Cable, 16ft (5 Meters) with probe weight for ExStik

*ExStik® Conductivity cell is not interchangeable with other ExStik® meters



EXTECH INSTRUMENTS CORPORATION
285 Bear Hill Road, Waltham, MA 02451-1064, U.S.A.
Phone: 781-890-7440 • FAX 781-890-7864
ISO 9001:2000 CERTIFIED

Make mine an Extech!™
www.extech.com

02/16/06 - R3