

# Signet 8750 pH/ORP Transmitters



Check out the 9900 Transmitter for your single channel needs

Member of the ProcessPro® Family of Instruments



Panel Mount



Pipe, Tank, Wall Mount

The Signet 8750 pH/ORP Transmitter is designed for broad application and ease of setup and use. The unit auto-configures for either pH or ORP use when connected to Signet pH or ORP electrodes. Multiple mounting options allow for installation best suited to your particular application.

The EasyCal menu features automatic buffer recognition for mistake-proof pH or ORP electrode calibrations. Intuitive software and the four button keypad arrangement make it easy to access important information such as pH or ORP, mV input, temperature, calibration, relay setup menus and more.

## Features

- Two 4 to 20 mA outputs
- Automatic temperature compensation
- Temperature display in °C or °F
- Hold and simulate functions
- Output scalability
- NEMA 4X/IP65 enclosure with self-healing window
- EasyCal



## Applications



- Neutralization Systems
- Heavy Metals Recovery
- Plating Control
- Scrubber Control
- Pool and Spa Control
- Environmental Study
- Water Treatment
- Water Quality Monitoring
- Waste Treatment
- Disinfection

# Specifications


General			
Accuracy	±0.03 pH, ±2 mV ORP		
Display	2 x 16 LCD		
	Contrast	User selectable, 5 levels	
Material			
Case	PBT		
Panel and Case Gasket	Neoprene		
Window	Polyurethane coated polycarbonate		
Keypad	Sealed 4-key silicone rubber		
Electrical			
Power	12 to 24 VDC ±10% regulated		
	60 mA max.		
Electrode Input Range	pH	0 to 14 pH	
	Temp.	3K Balco, -25 °C to 120 °C	-13 °F to 248 °F
	ORP	-1000 to +2000 mV, isolated	10 KΩ I.D. resistance T+, T-
Current Output	Dual 4 to 20 mA, isolated, passive, fully adjustable and reversible		
	Max. Loop Impedance	50 Ω max. @ 12 V	325 Ω max. @ 18 V    600 Ω max. @ 24 V
	Update Rate	0.5 seconds	
	Accuracy	±0.03 mA @ 25 °C, 24 V	
Open-Collector Output	High, Low, Pulse, Off		
	Optically isolated, 50 mA max, sink, 30 VDC max. pull-up voltage.		
	Hysteresis	User-adjustable Max. 400 pulses/min.	
Environmental			
Operating Temperature	-10 °C to 70 °C	14 °F to 158 °F	
Storage Temperature	-15 °C to 80 °C	5 °F to 176 °F	
Relative Humidity	0 to 95%, non-condensing		
Enclosure	NEMA 4X/IP65 (front face only on panel mount); field mount is 100% NEMA 4X/IP65		
Shipping Weight			
	0.6 kg	1.3 lb	
Standards and Approvals			
	CE, FCC, UL, CUL		
	RoHS compliant, China RoHS		
	Manufactured under ISO 9001 for Quality and ISO 14001 for Environmental Management and OHSAS 18001 for Occupational Health and Safety		

# Dimensions

## 3-8750-XP Panel Mount



## Field version with Universal Mounting Kit



### System Overview

#### In-line Installation

#### Wet-Tap Installation


#### Submersible Installation

	Panel Mount	Pipe, Tank, Wall Mount	Panel Mount	Pipe, Tank, Wall Mount	Panel Mount
Signet Instrument 8750		Signet pH/ORP Transmitter 8750 with 3-8050 Universal Mount Kit	Signet Instrument 8750	Signet pH/ORP Transmitter 8750 with 3-8050 Universal Mount Kit	Signet Instrument 8750
Signet Preamplifier 2760			Signet 2760 Preamplifier with Signet Wet-Tap Electrode 2756 2757		Signet 2760 Preamplifier with customer supplied pipe extension or conduit, 3/4 in. NPT or ISO 7/1-R 3/4 threads**
Signet Electrodes 2724-2726 2764-2767 2774-2777			Signet 3719 Wet-Tap		Signet Electrodes 2724-2726 2764-2767 2774-2777
GF Fittings* or customer supplied fittings			GF Tees and Fittings see model 3719 for more info		 All sold separately

\*See fittings section for more information.

\*\*Refer to the Signet Submersion Kit brochure (3-0000.707) located on our website for installation suggestions and options.

## Ordering Information



Mfr. Part No.	Code	Input	Output	Power
Field Mount pH/ORP Transmitter yellow body for pipe, wall, or tank mounting				
3-8750-3	<b>159 000 057</b>	One	Two 4 to 20 mA outputs and 2 open collectors	4 wire
Panel Mount pH/ORP Transmitter black body; including mounting bracket and panel gasket				
3-8750-3P	<b>159 000 058</b>	One	Two 4 to 20 mA outputs and 2 open collectors	4 wire

Please refer to **Wiring, Installation, and Accessories** sections for more information.

### Model 8750 Ordering Information

- 1) For panel version, cutout should be 92 x 92 mm (3.62 x 3.62 in.)
- 2) To mount the panel version on a wall, use the heavy duty wall mount bracket.
- 3) An optional splashproof rear cover can be ordered separately if needed - panel mount version only.
- 4) Use the universal mounting kit with the field mount instrument to mount to a pipe, tank or wall.

## Accessories and Replacement Parts

Mfr. Part No.	Code	Description
<b>Mounting</b>		
3-8050	<b>159 000 184</b>	Universal mounting kit
3-8050.392	<b>159 000 640</b>	¼ DIN retrofit adapter
3-8050.395	<b>159 000 186</b>	Splashproof rear cover (panel mount only)
3-0000.596	<b>159 000 641</b>	Heavy duty wall mount bracket (panel mount only)
3-5000.399	<b>198 840 224</b>	Panel adapter, 5 x 5 in. to ¼ DIN
3-5000.598	<b>198 840 225</b>	Surface mount bracket (panel mount only)
3-9900.396	<b>159 001 701</b>	Angle adjustment adapter kit
<b>Liquid Tight Connectors</b>		
3-9000.392	<b>159 000 368</b>	Liquid tight connector kit for rear cover (3 connectors)
3-9000.392-1	<b>159 000 839</b>	Liquid tight connector kit, NPT (1 connector)
3-9000.392-2	<b>159 000 841</b>	Liquid tight connector kit, PG 13.5 (1 connector)
<b>Other</b>		
3-0700.390	<b>198 864 403</b>	pH buffer kit (1 each 4, 7, 10 pH buffer in powder form, makes 50 ml of each)
3822-7115	<b>159 001 606</b>	20 gm bottle quinhydrone for ORP calibration (must use pH 4.01 and/or pH 7.00 buffer solutions)

3-8750.099 Rev F (02/16)

© Georg Fischer Signet LLC

3401 Aero Jet Avenue, El Monte, CA 91731-2882 U.S.A. • Tel. (626) 571-2770 • Fax (626) 573-2057 • www.gfsignet.com • e-mail: signet.ps@georgfischer.com  
 Specifications subject to change without notice. All rights reserved. All corporate names and trademarks stated herein are the property of their respective companies.