



# MiniRAE® Lite +

## Portable Handheld VOC Monitor

The MiniRAE Lite + is one of the most reliable handheld volatile organic compound (VOC) monitors on the market. Its photoionization detector's (PID) range of 0 to 5,000 ppm makes it an ideal instrument for applications ranging from environmental to construction.

### ADDITIONAL ADVANTAGES

- Duty-cycling™ lamp and sensor auto-cleaning technology
- Tough, flexible inlet Flexi-Probe™
- Large keys are operable with 3 layers of gloves
- Strong, built-in sample pump draws up to 100' (30m) horizontally or vertically
- Loud, 95 dB audible alarm
- Bright red flashing visible alarm
- Interchangeable drop-in Lithium-ion and alkaline battery packs
- 3-year 10.6 eV lamp warranty



- Accurate VOC monitoring
- Fast response time (3 sec)
- Humidity compensation
- Easy to maintain and operate
- Three-year lamp warranty
- Reflex PID Technology™

## FEATURES & BENEFITS

- |  |  |  |  |  |
|--|--|--|--|--|
| <ul style="list-style-type: none"> <li>• Proven PID technology           <ul style="list-style-type: none"> <li>– The patented sensor provides the following unique features:               <ul style="list-style-type: none"> <li>– 3-second response time</li> <li>– Range up to 5,000 ppm</li> <li>– Humidity compensation</li> </ul> </li> </ul> </li> </ul> | <ul style="list-style-type: none"> <li>– Six-month datalogging</li> <li>• Designed for service           <ul style="list-style-type: none"> <li>– Easy access to lamp and sensor in seconds without tools</li> </ul> </li> <li>• Big graphic display for easy overview of concentration</li> </ul> | <ul style="list-style-type: none"> <li>• Field-interchangeable battery pack, replaceable in seconds without tools</li> <li>• Integrated flashlight for better visibility in low light</li> </ul> | <ul style="list-style-type: none"> <li>• Multi-language support with 12 languages encoded</li> <li>• Rugged housing withstands use in harsh environments:           <ul style="list-style-type: none"> <li>– IP-65 design</li> </ul> </li> </ul> | <ul style="list-style-type: none"> <li>– Strong, protective removable rubber boot</li> </ul> |
|--|--|--|--|--|

# MiniRAE Lite + Specifications

SENSOR SPECIFICATIONS			
GAS MONITOR	RANGE	RESOLUTION	RESPONSE TIME
VOCS	0 to 999.9 ppm	0.1 ppm	< 3 sec
VOCS	1000 to 5,000 ppm	1 ppm	< 3 sec

  

MONITOR SPECIFICATIONS	
SIZE	10" L x 3.0" W x 2.5" H (25.5 x 7.6 x 6.4 cm)
WEIGHT	26 oz (738 g)
SENSORS	Photoionization sensor with standard 10.6eV lamp
BATTERY	- Alkaline battery adapter - External field-replaceable lithium-ion battery pack, if specified
OPERATING HOURS	12 hours of operation on alkaline battery adapter (12 hours with lithium-ion battery pack)
DISPLAY GRAPHIC	4 lines, 28 x 43 mm, with LED back light
KEYPAD	1 operation and 2 programming keys, 1 flashlight on/off
DIRECT READOUT	Instantaneous reading of: - VOCs as ppm by volume - High and low values - Date and time
ALARMS	95 dB buzzer (at 30 cm) and flashing red LED to indicate exceeded preset limits - High: 3 beeps and flashes per second - Low: 2 beeps and flashes per second - Alarm latching with manual override or automatic reset - Additional diagnostic alarm and display message for low battery and pump stall
EMI/RFI	- Highly resistant to EMI/RFI. - Compliant with EMC directive 89/336/EEC
IP RATING	IP-65
DATALOGGING	Standard 6 months at one-minute intervals
CALIBRATION	Two-point calibration for zero and span. Patented AutoZero feature
SAMPLING PUMP	- Internal, integrated flow rate at 400 cc/min - Sample from 100' (30m) horizontally and vertically
LOW FLOW ALARM	Auto shut-off pump at low-flow condition
WIRELESS NETWORK	* Bluetooth Low Energy (option)
SAFETY CERTIFICATION	ATEX II 2G EEx ia IIC T4
WIRELESS RANGE (typical)	Up to 15 ft (5m) for BLE
OPERATING TEMPERATURE	-4° to 113° F (-20° to 50° C)
HUMIDITY	0 to 95% relative humidity (non-condensing)
ATTACHMENTS	Durable green rubber boot
WARRANTY	3 years for 10.6 eV lamp, 1 year for pump, battery and instrument

Specifications are subject to change.

## MINIRAE LITE + ORDERING OPTIONS

### Monitor only includes:

- MiniRAE Lite + Monitor, Model PGM-7300
- RAE Systems 10.6 eV UV lamp
- Flex-I-Probe
- External filter
- Green rubber boot
- Alkaline battery adapter
- Lamp cleaning kit
- Tool kit
- Lithium-ion (Li-ion) battery, if specified with universal AC/DC charger and international plug kit
- Travel charger, if specified
- Universal wall adapter, if specified
- Operation & Maintenance manual
- Soft leather carrying case

### Monitor with accessories kit adds:

- Hard transport case with pre-cut foam padding
- 5 Porous metal filters and O-rings
- Gas outlet port adapter and tubing

### Optional calibration kit adds:

- 100 ppm isobutylene calibration gas, 34L
- Calibration regulator and flow controller

### For more information

www.honeywellanalytics.com  
www.raesystems.com

### Europe, Middle East, Africa

Life Safety Distribution GmbH  
Tel: 00800 333 222 44 (Freephone number)  
Tel: +41 44 943 4380 (Alternative number)  
Middle East Tel: +971 4 450 5800 (Fixed Gas Detection)  
gasdetection@honeywell.com

### Americas

Honeywell Analytics Distribution Inc.  
Tel: +1 847 955 8200  
Toll free: +1 800 538 0363  
detectgas@honeywell.com  
Honeywell RAE Systems  
Phone: +1 408 952 8200  
Toll Free: +1 888 723 4800

### Asia Pacific

Honeywell Analytics Asia Pacific Tel:  
+82 (0) 2 6909 0300  
India Tel: +91 124 4752700  
China Tel: +86 10 5885 8788-3000  
analytics.ap@honeywell.com

### Technical Services

EMEA: HAexpert@honeywell.com US:  
ha.us.service@honeywell.com AP:  
ha.ap.service@honeywell.com

Datasheet\_MiniRAE\_Lite+\_DS-1019-04\_EN  
10/18 ©2018 Honeywell International Inc.