




GEO **Calibration**

Model 2000 SHR

PRODUCT OVERVIEW

GENERAL SPECIFICATIONS

| | | | | |
|---|--------------------|---|--|--------------------------|
| CALIBRATION TO (17025 TRACEABLE TO NIST) | TRANSFER STANDARD | No Charge | | |
| | CERTIFICATE | 17025 Validation (Additional Fees Apply) | | |
| OPERATING AMBIENT CONDI- TIONS | TEMPERATURE | 18 °C to 28 °C | | |
| | HUMIDITY | Up to 80 % RH | | |
| STORAGE CONDITIONS | TEMPERATURE | -20 °C to 50 °C | | |
| | HUMIDITY | 0 % to 95 % RH (non-condensing) | | |
| ALTITUDE | 2000 m | | | |
| CALIBRATION SYSTEM ACCURACY | TEMPERATURE | ± 0.10 °C Or Better | Typically ± 0.05 °C | *Based on Probe Accuracy |
| | HUMIDITY | ± 1.00 % RH Or Better | Specially tuned systems can be as good as ± 0.60 % | *Based on Probe Accuracy |
| | CONTROLLER TYPE | PID Controller | | |
| UNIFORMITY | TEMPERATURE | 0.10 °C Or Better | Typically ± 0.05 °C | |
| | HUMIDITY | 0.30 % RH @ 18 °C to 28 °C Or Better Typically ± 0.25 % | | |
| STABILITY | TEMPERATURE | 0.05 °C | | |
| | HUMIDITY | 0.15 % RH @ 18 °C to 28 °C | | |
| WARM-UP PERIOD | AMBIENT CONDITIONS | 30 Minutes Maximum | | |
| | COLD | 30 Minutes | | |
| RESOLUTION | DISPLAY | Temperature | 0.01 °C | |
| | | Humidity | 0.01 % RH | |
| | | Dew Point | 0.01 °C (Calculated) | |
| | USB | Temperature | 0.01 °C | |
| | | Humidity | 0.01 % RH | |



RAMP / SOAK RATE OF CHANGE

*Depends on ambient and desiccant conditions

| | | |
|-------------|------------|------------------------------|
| TEMPERATURE | High → Low | 1.50 °C / minute *Typical |
| | Low → High | 5.00 °C / minute *Typical |
| HUMIDITY | High → Low | 5.00 % RH / minute *Typical |
| | Low → High | 10.00 % RH / minute *Typical |

CONTROL RANGE

| | | | |
|----------------|----------------|----------------|----------------|
| TEMPERATURE | 5 °C to 55 °C | | |
| HUMIDITY@ 18°C | 5 % to 95 % RH | HUMIDITY@ 35°C | 5 % to 80 % RH |
| HUMIDITY@ 23°C | 5 % to 95 % RH | HUMIDITY@ 40°C | 5 % to 75 % RH |
| HUMIDITY@ 30°C | 5 % to 85 % RH | HUMIDITY@ 50°C | 5 % to 60 % RH |

CONSUMABLES

| | | |
|---------------|-----------------------|---|
| WATER | RESERVOIR | 200 ml |
| | SPILL RESISTANT | Yes |
| | REQUIRED FLUID | Distilled Water Only |
| | EST. REFILL PERIOD | 15 Days to 1 Month (Typical) *Depends on Usage |
| | FILL INDICATOR | Floating Ball |
| DESICCANT | TYPE | Molecular Sieve |
| | REPLACEMENT | When Indicating Desiccant is 3/4 Used |
| | REPLACEMENT FREQUENCY | Depends Entirely on User Workload |
| | LOCATION | Front Mounted |
| RECALIBRATION | FREQUENCY | Depends on User Uncertainty Requirements Once Per Year Recommended |

**Information subject to change, please visit our website for updates at www.geocalibration.com.

MECHANICAL

| | Measurement Type | Width | Depth | Height |
|---------------------------------------|------------------|--|-----------------------|----------------------|
| GENERATOR DIMENSIONS | Metric | 55.33 cm | 40.65 cm | 24.65 cm |
| | English | 21.78 in | 16.02 in | 9.70 in |
| | Measurement Type | Diameter | Depth | |
| CHAMBER DIMENSIONS | Metric | 14.50 cm | 20.00 cm | |
| | English | 5.71 in | 7.87 in | |
| | Measurement Type | Diameter | Depth | |
| WORKING DIMENSIONS AND VOLUME | Metric | 12.50 cm | 10.90 cm | |
| | English | 4.92 in | 4.29 in | |
| | Volume | 1.5 Liter Effective Working Volume | | |
| WEIGHT | Unit Only | Metric | 15.5 kg | |
| | | English | 34.0 lb | |
| POWER SUPPLY | Power Supply | 12 Volt DC @ 1A | | |
| STANDARD PORT QUANTITY | Depends on doors | Availability: 6 Ports, 5 Ports, 4 Ports, 2 Ports | | |
| CHILLED MIRROR PORTS | In and Out | | | |
| | | Probe Range | Actual Unit Range | |
| PROBE ANALOG OUTPUTS AVAILABLE | 0 - 1 Volt | Temperature | - 40.00 to + 60.00 °C | + 5.00 to + 55.00 °C |
| | | Humidity | 0 to + 100.00 % | + 5.00 to + 95.00 % |

Ordering Information

Standard Supply Package

*Customization is Available

* Complete Accessory List is Available at www.geocalibration.com

| | | |
|--|--------------------|-----------------------|
| Square 5-Port Door | Desiccant Canister | Fill Syringe |
| 7 Grommets (1/8", 1/4", 3/8", 1/2", 5/8", 3/4", 7/8") | Mains Power Cord | Calibration Documents |

Accessories

| Doors | Shape | Port Quantity | Connector Type | Part Number | | | | |
|-------------------|---|---------------------------|----------------------------------|--|-----------|-----------|----------------|----------------|
| | Square / Round | 6-Port Door | M36 Connectors | 01-001-00-0017 / 01-001-00-0018 | | | | |
| | Square | 5-Port Door | M36 Connectors | 01-001-00-0013 | | | | |
| | Square / Round | 4-Port Door | M36 Connectors | 01-001-00-0003 / 01-001-00-0004 | | | | |
| | Square / Round | 4-Port Door | SLIMLINE | 01-001-00-0024 / 01-001-00-0025 | | | | |
| | Square | 4-Port Chilled MirrorDoor | M36 Connectors | 01-001-00-0010 | | | | |
| | Square | 2-Port Door | M36 Connectors | 01-001-00-0028 | | | | |
| Grommets | Port Type | Size (in) | Size (mm) | Part Number | Port Type | Size (in) | Size (mm) | Part Number |
| | M36 | 0.000" | 0.000 | 01-004-09-0001 | SLIMLINE | 0.125" | 3.175 | 01-004-09-0020 |
| | M36 | 0.125" | 3.175 | 01-004-09-0002 | SLIMLINE | 0.250" | 6.350 | 01-004-09-0021 |
| | M36 | 0.250" | 6.350 | 01-004-09-0003 | SLIMLINE | 0.375" | 9.525 | 01-004-09-0022 |
| | M36 | 0.375" | 9.525 | 01-004-09-0004 | SLIMLINE | 0.500" | 12.700 | 01-004-09-0023 |
| | M36 | 0.500" | 12.700 | 01-004-09-0005 | SLIMLINE | 0.625" | 15.875 | 01-004-09-0024 |
| | M36 | 0.625" | 15.875 | 01-004-09-0006 | SLIMLINE | 0.750" | 19.050 | 01-004-09-0025 |
| | M36 | 0.750" | 19.050 | 01-004-09-0007 | SLIMLINE | 0.825" | 20.950 | 01-004-09-0026 |
| | M36 | 0.875" | 22.225 | 01-004-09-0008 | SLIMLINE | 1.000" | 25.400 | 01-004-09-0027 |
| | M36 | 1.000" | 25.400 | 01-004-09-0009 | | | | |
| Expansion Chamber | Description | | | Width | Depth | Height | Part Number | |
| | Standard Expansion Chamber | | | 220mm | 286mm | 345mm | 01-054-00-0000 | |
| Additional | Description | | Part Number | Note: | | | | |
| | Desiccant Canister w/ Material Chamber Insert | | 01-201-11-0001 01-200-08-0025 | (Various Desiccant Canisters and Expansion Chamber Available For This Unit.) | | | | |

**Information subject to change, please visit our website for updates at www.geocalibration.com.



GEO
Calibration

Humidity Control Company



Proudly Made in the USA 

Email: Sales@GeoCalibration.com Website: www.GeoCalibration.com

© 2020 GEO Calibration Inc. All rights reserved.