

# ORBIT 60 SERIES Process Variable and Discrete Input Module

## Datasheet

Bently Nevada Machinery Condition Monitoring

145M9027 Rev. A



## Description

The Orbit 60 Series Isolated Process Variable and Discrete (PVD) Input module processes machine-critical parameters such as pressure, flow, temperature, and levels that merit continuous monitoring. The module conditions and digitizes the signals so the result can be compared with user-programmable alarm setpoints. The user can program the PVD module using the Orbit Configuration software to perform current, voltage or discrete input measurements. This module provides discrete inputs for essential operational commands, such as Trip Multiply for machine start-up and Alarm Inhibit.

The monitor accepts +4 to +20 mA current inputs or any proportional voltage inputs between -10 Vdc and +10 Vdc, in addition to monitoring “dry” or “wet” contacts which can be a sensor, switch, or relay.

Primary purposes of the PVD Module:

- Continuously process input from monitored parameters to be compared against configured alarm setpoints to drive alarms for machinery protection.
- Allow provision of essential machine information, such as Trip Multiply for machine startup and Alarm Inhibit for both operations and maintenance personnel.

These modules occupy a single slot. The module OK LEDs indicate proper functioning and the LINK LEDs indicate good system communication. Six Channel Status LEDs on the utility side of the module indicate a connected sensor in OK condition.



## Isolated Process Variable / Discrete Input





Isolated PV / Discrete Input (PVD)	
Power Consumption	
Typical	4.5 W
Maximum	6.5 W
Characteristics	
Channels	6
Isolation	500 V Channel to System and 250 V Channel to Channel isolation
Process Variable 4–20 mA Input	
Process Variable Input (Current)	4 to 20 mA
Error	±1% of Fullscale
Voltage Compliance	3 V
Fault Input Tolerance	±24 V
Powered off module input resistance	>10 MΩ
Powered on nominal Input resistance	100 Ω + 0.3V <sup>1</sup>
Process Variable -10V to +10V Input	
Process Variable Input (Voltage)	-10 to 10 Vdc 0 to 10 Vdc 2 to 10 Vdc 0 to 5 Vdc 1 to 5 Vdc -10 to 0 Vdc
Error	±1% of Fullscale


Isolated PV / Discrete Input (PVD)	
±10V Nominal Input Impedance	249 kΩ
Fault Input Tolerance	±40 V


<sup>1</sup> The voltage drop across the input when configured for a current input is 100 Ω x Input Current + 0.3 V.


Discrete Input	
Discrete Input	Dry Contact, Internally Wetted Wetted Contact, 0 to 10 Vdc
Internal Wetting Voltage	11.5 V to 12.7 V
Fault Input Tolerance	± 40 V

PVD Output	
Module OK LED	Indicates when the module is functioning properly
System Communication LED	Indicates when the module is communicating to the rest of the system
Channel Status LED (Rear Utility Side)	1 per input channel indicates when the connected sensor is in an OK condition

Environmental Limits	
Chassis Operating Temperature Range (indoor use only)	<p><b>3U Chassis:</b>            -30°C to +70°C            (-22°F to 158°F) </p> <p><b>6U Chassis:</b>            -30°C to +65°C            (-22°F to 149°F) </p>
Module Temperature Rating - Certification	<p>-30°C to +70°C            (-22°F to 158°F)</p> <div style="border: 1px solid black; padding: 5px; background-color: #e0f2f1;">  You must still meet the Chassis Operating Temperature Range defined above.         </div>
Storage Temperature Range	-40°C to +85°C (-40° F to 185° F)
Relative Humidity	0% to 95% rH non-condensing operating and storage
Vibration	<p>Without Isolators:            0 g to 0.35 g @ 57-500 Hz</p> <p>With Isolators:            0 g to 5 g @ 57-500 Hz.</p>
Shock	2" Incline Drop
Altitude	<p>&lt; 2000 m (6,562 ft)</p> <div style="border: 1px solid black; padding: 5px; background-color: #e0f2f1;">  Higher altitudes are possible but are site specific applications. Contact Bently Nevada support if you require higher altitudes.         </div>
Pollution Degree	Pollution Degree 2
Installation Category	Category II

 Verify that temperature ratings on the wiring cables match the operating temperature range.

 **CAUTION**



**LOCATION TEMPERATURE AND HUMIDITY**

If you install the hardware in a location where temperatures may exceed 40° C (104° F) or in excessive humidity, you should consider supplying environmental controls. High temperatures will reduce the operational life of the system.

## Compliance and Certifications

### FCC

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- This device may not cause harmful interference.
- This device must accept any interference received, including interference that may cause undesired operation.

### EMC

European Community Directive:

EMC Directive 2014/30/EU

Standards:

EN 61000-6-2; Immunity for Industrial Environments  
EN 61000-6-4; Emissions for Industrial Environments

### Electrical Safety

European Community Directive:

LV Directive 2014/35/EU

Standards:

EN 61010-1;  
EN 61010-2-201;

### RoHS

European Community Directive:

RoHS Directive 2011/65/EU

### Cyber Security

Designed to meet IEC 62443-4-2

### \*Maritime

ABS Rules for Condition of Classification, Part 1

- Steel Vessels Rules
- Offshore Units and Structures

\* Approvals pending

### Functional Safety

SIL 2

### Hazardous Area Approvals



For the detailed listing of country and product-specific approvals, refer to the [Approvals Quick Reference Guide \(108M1756\)](#).

For additional technical documentation, please log in to [bntechsupport.com](http://bntechsupport.com) and access the Bently Nevada Media Library.

### cNRTLus

Class I, Zone 2: AEx/Ex ec nC IIC T4 Gc;

Class I, Zone 2: AEx/Ex nA nC IIC T4 Gc;

Class I, Division 2, Groups A, B, C, D T4;

Class I, Division 2, Groups A, B, C, D T4 (N.I.);

T4 @ Ta= -30°C to +70°C (-22°F to +158°F)

### ATEX/IECEx



II 3 G

Ex ec nC IIC T4 Gc

Ex nA nC IIC T4 Gc

T4 @ Ta= -30°C to +70°C (-22°F to +158°F)

## Ordering Information



For the detailed listing of country and product-specific approvals, refer to the [Approvals Quick Reference Guide \(108M1756\)](#).

For additional technical documentation, please log in to [bntechsupport.com](http://bntechsupport.com) and access the Bently Nevada Media Library.

## Isolated Process Variable / Discrete Input Module (PVD)

Ordering Option	Description
60R/INP09	
<b>AAA – Hazardous Area Certifications</b>	
00	No Hazardous Area
01	CSA/NRTL/C (Class I, Div 2)
02	Multi (CSA, ATEX, IECEx)
XXX	Country Specific Approvals
<b>B – SIL Level</b>	
0	No SIL
2	SIL 2

Copyright 2023 Baker Hughes Company. All rights reserved.



Bently Nevada and Orbit Logo are registered trademarks of Bently Nevada, a Baker Hughes business, in the United States and other countries. The Baker Hughes logo is a trademark of Baker Hughes Company. All other product and company names are trademarks of their respective holders. Use of the trademarks does not imply any affiliation with or endorsement by the respective holders.

Baker Hughes provides this information on an "as is" basis for general information purposes. Baker Hughes does not make any representation as to the accuracy or completeness of the information and makes no warranties of any kind, specific, implied or oral, to the fullest extent permissible by law, including those of merchantability and fitness for a particular purpose or use. Baker Hughes hereby disclaims any and all liability for any direct, indirect, consequential or special damages, claims for lost profits, or third party claims arising from the use of the information, whether a claim is asserted in contract, tort, or otherwise. Baker Hughes reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation. Contact your Baker Hughes representative for the most current information.

The information contained in this document is the property of Baker Hughes and its affiliates; and is subject to change without prior notice. It is being supplied as a service to our customers and may not be altered or its content repackaged without the express written consent of Baker Hughes. This product or associated products may be covered by one or more patents. See [Bentley.com/legal](https://www.bentley.com/legal).

1631 Bently Parkway South, Minden, Nevada USA 89423  
Phone: 1.775.782.3611 (US) or [Bentley.com/support](https://www.bentley.com/support)  
[Bentley.com](https://www.bentley.com)