

# **BaleMaster**

# Digital Instrument for Rapid Assessment of Moisture Levels in Straw and Hay Bales



The Protimeter Digital BaleMaster is a handheld instrument which displays results on a large LCD Digital Display. It is supplied with a durable 600mm (24") stainless steel probe designed to reach the center of large bales.

#### **Features**

- Measurement range: 8.5% 36.8%
- Strong, robust stainless steel moisture probe
- · Easy to read digital display
- Colour arc LED display to show moisture condition:

Green (Dry)

Yellow (At Risk)

Red (Wet)

- Dual display LCD and LED for easy reading
- Audible tone





# **Amphenol**Advanced Sensors

# **BaleMaster Specifications**

# **Operating Conditions:**

- Operating temperature range: 0°C to 50°C
- Humidity: 0 to 90% RH, non-condensing

## **Measurement Range:**

• 8.5% to 36.8%

Green (Dry) 8.5-15%

Yellow (At Risk) 15.1-19.5%

Red (Wet) 19.6 - 36.8%

#### **Power:**

9V- Alkaline 550mAh

# **Dimensions and Weight**

- Size: 19cm x 6.5cm x 3.5cm (7.5" x 2.5" x 1.4")
- Gross Weight (without battery): ~228g (8oz)

#### **Probe Dimensions:**

- Length 5584mm (23")
- Diameter 10mm (0.4")

#### **Buzzer:**

User adjustable audible tone indicating moisture conditions

# **Regulatory Compliance:**

· CE, RoHS, ETL

### **Warranty:**

 2 years on mechanical or manufacturing defects. Does not include wearing parts or accessories

#### **Part Numbers:**

- GRN6165 Balemaster instrument and probe
- GRN6148 Balemaster probe









www.protimeter.com www.amphenol-sensors.com

© 2016 Amphenol Corporation. All Rights Reserved. Specifications are subject to change without notice