



Discrete I/O Modules (Input)

Input modules provide the interface between the PLC and external input devices such as proximity sensors, push buttons, switches, and BCD thumbwheels. Output modules provide the interface between the PLC and external output devices such as contactors, interposing relays, BCD displays and indicator lamps. GE offers a variety of modules that support different voltage ranges and types, current capacity, isolation and response time to meet your application needs.

	IC694ACC300	IC694MDL230	IC694MDL250	IC694MDL231	IC694MDL240
Product Name	PACSystems RX3i DC Voltage Input Simulator, 8/16 Points	PACSystems RX3i AC Voltage Input Module, 120 VAC Isolated, 8 Point Input	PACSystems RX3i AC Voltage Input Module, 120 VAC Isolated, 16 Point Input	PACSystems RX3i AC Voltage Input Module, 240 VAC Isolated, 8 Point Input	PACSystems RX3i AC Voltage Input Module, 120 VAC, 16 Point Input
Lifecycle Status	Active	Active	Active	Active	Active
Module Type	Input Simulator	Discrete Input	Discrete Input	Discrete Input	Discrete Input
Backplane Support	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1	1	1
Input Voltage Range	N/A	0-132 VAC	0-132 VAC	0-264 VAC	0-132 VAC
Input Current (mA)	N/A	14.5	14.5	15	12
Number of Points	16	8	16	8	16
Response Time (ms)	20 on/30 off	30 on/45 off	30 on/45 off	30 on/45 off	30 on/45 off
Trigger Voltage	N/A	74-132	74-132	148-264	74-132
Points per Common	16	1	1	1	16
Diagnostic Supported	N/A	N/A	N/A	N/A	N/A
Connector Type	Switches	Terminal Block (20 screws), included with module.	IC694TBBx32 or IC694TBSx32. Sold Separately.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.
Internal Power Used	120 mA @ 5 VDC	60 mA @ 5 VDC	60 mA @ 5 VDC	60 mA @ 5 VDC	90 mA @ 5 VDC



Discrete I/O Modules (Input)

Input modules provide the interface between the PLC and external input devices such as proximity sensors, push buttons, switches, and BCD thumbwheels. Output modules provide the interface between the PLC and external output devices such as contactors, interposing relays, BCD displays and indicator lamps. GE offers a variety of modules that support different voltage ranges and types, current capacity, isolation and response time to meet your application needs.

	IC694MDL260	IC694MDL241	IC694MDL632	IC694MDL634	IC694MDL645
Product Name	PACSystems RX3i AC Voltage Input Module, 120 VAC, 32 Point Input	AC/DC Voltage Input Module, 24 VAC/VDC	PACSystems RX3i DC Voltage Input Module, 125 VDC Pos/Neg Logic, 8 Point Input	PACSystems RX3i DC Voltage Input Module, 24 VDC Pos/Neg Logic, 8 Point Input	PACSystems RX3i DC Voltage Input Module, 24 VDC Pos/Neg Logic, 16 Point Input
Lifecycle Status	Active	Active	Active	Active	Active
Module Type	Discrete Input	Discrete Input	Discrete Input	Discrete Input	Discrete Input
Backplane Support	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions
Number of Slots Module Occupies on Backplane	1	1	1	1	1
Input Voltage Range	0-132 VAC	0-30 VDC	0-150 VDC	0-30 VDC	0-30 VDC
Input Current (mA)	12	7	4.5	7	7
Number of Points	32	16	8	8	16
Response Time (ms)	30 on/45 off	12 on/28 off	7 on/7 off	7 on/7 off	7 on/7 off
Trigger Voltage	74-132	11.5-30	90-150	11.5-30	11.5-30
Points per Common	16	16	4	8	16
Diagnostic Supported	N/A	N/A	N/A	N/A	N/A
Connector Type	IC694TBBx32 or IC694TBSx32. Sold Separately.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.	Terminal Block (20 screws), included with module.
Internal Power Used	90 mA @ 5 VDC	80 mA @ 5 VDC; 125 mA @ 24 VDC	40 mA @ 5 VDC	45 mA @ 5 VDC; 62 mA @ 24 VDC Isolated Isolated	80 mA @ 5 VDC; 125 mA @ 24 VDC Isolated



Discrete I/O Modules (Input)

Input modules provide the interface between the PLC and external input devices such as proximity sensors, push buttons, switches, and BCD thumbwheels. Output modules provide the interface between the PLC and external output devices such as contactors, interposing relays, BCD displays and indicator lamps. GE offers a variety of modules that support different voltage ranges and types, current capacity, isolation and response time to meet your application needs

	IC694MDL646	IC694MDL654	IC694MDL655	IC694MDL660	IC695MDL664
Product Name	PACSystems RX3i DC Voltage Input Module, 24 VDC Pos/Neg Logic, FAST, 16 Point Input	PACSystems RX3i DC Voltage Input Module, 5/12 VDC (TTL) Pos/Neg Logic, 32 Point Input	PACSystems RX3i DC Voltage Input Module, 24 VDC Pos/Neg Logic, 32 Point Input	PACSystems RX3i DC Voltage Input Module, 24 VDC Pos/Neg Logic, 32 Point Input	PACSystems RX3i DC Voltage Input Module, 24VDC Positive Logic, Advanced Diagnostics, 16 Point Input
Lifecycle Status	Active	Active	Active	Active	Active
Module Type	Discrete Input	Discrete Input	Discrete Input	Discrete Input	Discrete Input
Backplane Support	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions	No Backplane Restrictions	Universal PCI Slot Only
Number of Slots Module Occupies on Backplane	1	1	1	1	1
Input Voltage Range	0-30 VDC	0-15 VDC	0-30 VDC	0-30 VDC	0-30 VDC
Input Current (mA)	7	3.0 @ 5 V, 8.5 @ 12 V	7	7	12.2
Number of Points	16	32	32	32	16
Response Time (ms)	1 on/1 off	1 on/1 off	2 on/2 off	0.5ms, 1.0ms, 2.0ms, 5ms, 10ms, 50ms and 100ms, selectable per module. On and off.	0.5ms, 1.0ms, 2.0ms, 5ms, 10ms, 50ms and 100ms, selectable per module. On and off.
Trigger Voltage	11.5-30	4.2-15	11.5-30	11.5-30	0.5 × VIN VDC
Points per Common	16	8	8	8	8
Diagnostic Supported	N/A	N/A	N/A	N/A	Open Wire, Short to DC Negative Input Pulse Test Short to DC Plus
Connector Type	Terminal Block (20 screws), included with module.	Fujitsu Connector	Fujitsu Connector	IC694TBBx32 or IC694TBSx32. Sold Separately.	IC694TBB032 or IC694TBS032
Internal Power Used	80 mA @ 5 VDC; 125 mA @ 24 VDC Isolated	5 VDC -195 mA @ 5 VDC; 12 VDC -440 mA @ 5 VDC	195 mA @ 5 VDC	300 mA @ 5 VDC	225 mA @ 5 VDC; 95 mA @ 3.3 VDC