

SCT-20

SIGNAL CONDITIONING
TRANSMITTERS



RICE LAKE
WEIGHING SYSTEMS

To be the best by every measure®

800-472-6703
www.ricelake.com
m.ricelake.com

SCT-20

SIGNAL CONDITIONING TRANSMITTERS



Control in miniature

For PLC systems that require weight data from a scale, Rice Lake's compact SCT transmitters deliver equivalent signal-conditioning function without the cost or bulk of a full size weight indicator/controller.

Each Rice Lake SCT is DIN Rail mountable within a cabinet or control panel, where it converts a scale's load cell signals to analog

output, serial output, or a specific network protocol. Unlike many other signal transmitters, Rice Lake's SCT has its own .3 inch weight display, with annunciators for unit and weighing status, and push buttons for zero, tare and setpoint entry, simplifying scale setup, calibration and operation.

Standard Features

- Powers up to eight load cells in parallel (with a 24 bit A/D converter)
- RS-485 or RS-232 serial output, supports ASCII and Modbus RTU
- 16-bit analog output resolution
- Diagnostic message for load cell disconnect and over capacity errors
- Analog outputs for displayed weight of 0-20mA, 4-20mA, 0-10V, 0-5V or +/-10V and +/-5V, selected as voltage or current, can track positive or negative weight values
- Two digital inputs that can be set as gross/net, zero, peak weight or print
- Three dry contract relay outputs capable of driving up to 150ma at 115VAC
- Single channel indicator

SCT-20 Optional Protocols

- Analog Output
- Ethernet TCP/IP
- EtherNet/IP (ODVA Certification)
- DeviceNet
- Profibus DP
- Modbus/TCP

Specifications SCT-20

A/D SAMPLE RATE: 300 Hz (Adjustable with filter settings 0-9)

RESOLUTION:

Internal Resolution: 16 million counts
Weight Display Resolution: 999,999
System Linearity: ± 0.01% full scale

DIGITAL INPUTS/OUTPUTS:

2 inputs 5-24VDC,
3 outputs 115 VAC/150mA
N.O. or N.C. (dry contact)

DISPLAY:

0.3in (8mm), six-digit, 7 segment LED

ANNUNCIATORS:

Net, center of zero, stability, KG, G, LB

KEYBOARD:

4-key push-button panel, tactile feel
Zero, Tare, Print, Menu, Escape, Left & Up Navigation, Enter

OPERATING TEMPERATURE & HUMIDITY:

Working Temperature: -4°F to 140°F (-20°C to 60°C)
Humidity: 85% non-condensing

DIMENSIONS (W x H x D):

SCT Converter: 0.98 x 4.52 x 4.72 in (25 x 115 x 120mm)


RATING/MATERIAL:

SCT Enclosure: NEMA 1 plastic pluggable connectors

WARRANTY:

One-year limited warranty

Approvals



Your Rice Lake Weighing Systems distributor is:

RICE LAKE
WEIGHING SYSTEMS
To be the best by every measure®

230 W. Coleman St. • Rice Lake, WI 54868 • USA
TEL: 715-234-9171 • FAX: 715-234-6967 • www.ricelake.com

An ISO 9001 registered company © 2014 Rice Lake Weighing Systems PN 159035 4/14
Specifications subject to change without notice.