

Floor Scale and Indicator Package

Specifications

Summit 3000 Floor Scale

End Load Capacity

- 100% full scale at 5,000 lb (2,500 kg)
- 80% full scale at 10,000 lb (5,000 kg)

Cable Length:

- 20 ft (6.1 m) (for connecting junction box to indicator)

Warranty:

- Summit 3000 weldment and load cells two years, all other components one year

Approvals:

- NTEP CC 92-001A9, Class III 5,000 d
- Measurement Canada AM-5530, Class III 5,000 d

120/120 Plus Digital Weight Indicator

Power:

120/120 Plus:

- Line voltages: 115 or 230 VAC
- Frequency: 50 or 60 Hz
- 120 Plus: (estimated battery life)
- 60 hours with 1 x 350 Ω
- 40 hours with 4 x 350 Ω
- Charge time 8 hours

Operating Temperature:

- Legal: 14° F to 104° F (-10° C to 40° C)
- Industrial: 14° F to 122° F (-10° C to 50° C)

Rating/Material:

- Enclosure: heavy gauge ABS

Warranty:

- One-year limited warranty

120 Approvals:

- NTEP CC 03-059, Class III/IIIL 6,000 d
- Measurement Canada AM-5517, Class III/IIHD 6,000 d OIML TC7028 T 5692, 5,000 d
- CE marked

120 Plus Approvals:

- NTEP CC 03-059, Class III/IIIL 6,000 d
- Measurement Canada AM 5517
- OIML TC 7626, T5692 5,000 d Class III/IIHD 6,000 d



Package is configured, corner-trim, and calibrated for 5,000 divisions before shipping

Floor Scale and Indicator Package

Package includes Summit® 3000 floor scale, 120 PLUS digital weight indicator with tilt stand, 20 ft load cell cable with quick disconnect, configured and calibrated

INDICATOR APPROVALS



Measurement
Canada
Approved



Standard Features

Summit® 3000 Floor Scale

- 4 NTEP Certified alloy steel-shear beam load cells
- Top access junction box
- Rugged diamond safety treadplate steel deck
- 4 adjustable rigid polyurethane rubber feet, 3 in (76.2 mm) diameter
- Signal trim summing board housed in ABS enclosure
- Threaded eyebolt hole (1/2-20NF) located in the center of the deck for easy lifting
- 20 ft of EL147 load cell cable with quick disconnect
- Package configured and calibrated for 5,000 divisions

120 Digital Weight Indicator

- Large .8 in (20.3 mm) light emitting diode (LED) display
- 5-button operation
- Full front panel digital calibration and configuration

120 PLUS Digital Weight Indicator

- Large .8 in backlit liquid crystal display (LCD)
- 115 or 230 VAC wall adapter with rechargeable battery

Floor Scale and Indicator Package

Part Number/Price

PART #	SIZE (W X L X H)	CAPACITY	EST. SHIP WEIGHT	PRICE
Floor Scale and Indicator Package (Single Scale)				
Package includes Summit® 3000 floor scale, 120/120 PLUS digital weight indicator with tilt stand, 20 ft load cell cable with quick disconnect, configured and calibrated				
115 VAC (120)				
78772	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	315 lb	Consult
78773	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	315 lb	Consult
115 VAC (120 PLUS)				
106913	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	315 lb	Consult
106914	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	315 lb	Consult
230 VAC (120)				
78780	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	315 lb	Consult
78781	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	315 lb	Consult
230 VAC (120 PLUS)				
106915	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	315 lb	Consult
106916	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	315 lb	Consult
115 VAC Canadian Weights and Measures (120)				
78776	4 ft x 4 ft x 3.625 in	2,500 lb x 0.5 kg	315 lb	Consult
78777	4 ft x 4 ft x 3.625 in	5,000 lb x 1 kg	315 lb	Consult
115 VAC Canadian Weights and Measures (120 PLUS)				
106917	4 ft x 4 ft x 3.625 in	2,500 lb x 0.5 kg	315 lb	Consult
106918	4 ft x 4 ft x 3.625 in	5,000 lb x 1 kg	315 lb	Consult
Floor Scale and Indicator Package (5-Scale Package)				
Packages include five Summit® 3000 floor scales, five 120/120 Plus digital weight indicators with tilt stands, five 20 ft load cell cables with quick disconnect, configured and calibrated				
115 VAC (120)				
78774	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	1665 lb	Consult
78775	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	1665 lb	Consult
115 VAC (120 PLUS)				
106929	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	1665 lb	Consult
106930	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	1665 lb	Consult
230 VAC (120)				
78782	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	1665 lb	Consult
78783	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	1665 lb	Consult
230 VAC (120 PLUS)				
106931	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	1665 lb	Consult
106932	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	1665 lb	Consult
115 VAC Canadian Weights and Measures (120)				
78778	4 ft x 4 ft x 3.625 in	2,500 kg x 0.5 kg	1665 lb	Consult
78779	4 ft x 4 ft x 3.625 in	5,000 kg x 1 kg	1665 lb	Consult
115 VAC Canadian Weights and Measures (120 PLUS)				
106933	4 ft x 4 ft x 3.625 in	2,500 kg x 0.5 kg	1665 lb	Consult
106934	4 ft x 4 ft x 3.625 in	5,000 kg x 1 kg	1665 lb	Consult

Options/Accessories

PART #	DESCRIPTION	PRICE
Summit® 3000 Floor Scale		
75819	Floor anchor plates, mild steel (set of 2)	Consult
76012	Additional operating manual	Consult
120 Digital Weight Indicator		
77925	Revolution® scale software*	Consult
103636	Power supply, 120 Plus wall adapter, 115/230 VAC, 5 VDC	Consult
76699	Additional operating manual	Consult

* Revolution® III can be downloaded for free from the dealer section of our website at www.ricelake.com

Access ramps, pit frames, bumper guards and portability frames available, see end of section for details