

Fill in the form below, complete sections 1 through 7 and email to: [veris-sales@armstronginternational.com](mailto:veris-sales@armstronginternational.com)

Requested By: \_\_\_\_\_

Date: \_\_\_\_\_ Tag#: \_\_\_\_\_ E-mail: \_\_\_\_\_


Phone: \_\_\_\_\_ Fax: \_\_\_\_\_

Company: \_\_\_\_\_ Address: \_\_\_\_\_ City, State, Zip: \_\_\_\_\_

End User:

Company Name: \_\_\_\_\_ City: \_\_\_\_\_ State, Zip: \_\_\_\_\_

## 1. Enter Pipe Dimensions




Pipe Size \_\_\_\_\_ Sch \_\_\_\_\_  
 Pipe ID \_\_\_\_\_ Wall \_\_\_\_\_ Pipe Mat'l \_\_\_\_\_  
 Wall

## 2. Pipe Orientation

(Check one box)



(H) Horizontal



(V) Vertical

## 3. Enter Flow Conditions

Fluid Name:		Maximum	Normal	Minimum	Units
<b>Flow Rate</b>					
<b>All Fluids</b>	Pressure @ Flow				
	Temperature @ Flow				
<b>Gas</b>	Specific Gravity, or				
	Molecular Weight				
<b>Liquid</b>	Specific Gravity				
<b>Steam</b>	VeraCalc Program can calculate Density from Temperature and Pressure				

**Special Instructions**

## 4. Select Model Accelabar 316SS


(Check one box in each category)

AFS Flanged (ANSI):

- 150#     300#  
 600#     ABS Bevel for Weld  
 ATS MNPT Threaded Ends (1" and 2" meter only)

Specify Accelabar Meter Size:

- 1" (DN25)     6" (DN150)  
 2" (DN50)     8" (DN200)  
 3" (DN75)     10" (DN250)  
 4" (DN100)     12" (DN300)



## 5. Select Instrument Head

(Check one box)

Instrument Head Connections (Select Remote or Direct Mount Transmitter — Sold Separately)				
Direct Mount Transmitter (Flanged 450°F/232°C Max.)		Remote Mount Transmitter (1/2" NPT)		
Manifold	Transmount	Valve	Regular	Parallel
Integral		Integral		
<input type="checkbox"/> M	<input type="checkbox"/> F	<input type="checkbox"/> T	<input type="checkbox"/> R	<input type="checkbox"/> P

## 6. Select Instrument Valves or Manifold, RTD & Cable (Optional)

Manifolds (Optional)				Instrument Valves (Optional)	
Direct Mount				Remote Mount	
3-Valve		5-Valve		Needle	Gate
Soft Seat	Hard Seat	Soft Seat	Hard Seat	1/2" NPT	1/2" NPT
<input type="checkbox"/> F3SC (CS) <input type="checkbox"/> F3SS (SS)	<input type="checkbox"/> F3HC (CS) <input type="checkbox"/> F3HS (SS)	<input type="checkbox"/> F5SC (CS) <input type="checkbox"/> F5SS (SS)	<input type="checkbox"/> F5HC (CS) <input type="checkbox"/> F5HS (SS)	<input type="checkbox"/> C2NC (CS) <input type="checkbox"/> C2NS (SS)	<input type="checkbox"/> C2GC (CS) <input type="checkbox"/> C2GS (SS)

Code	RTD in Thermowell
<input type="checkbox"/> H1	Standard Temperature, 500°F (260°C) Max., Explosion Resistant High Temperature, 900°F (482°C) Max., Moisture and Dust Resistant
<input type="checkbox"/> HT	
Code	Connection Cable to Transmitter (Direct Mount Only)
<input type="checkbox"/> XP	Explosion Resistant
<input type="checkbox"/> N4	Moisture and Dust Resistant

## 7. Transmitter

Supplied By
<input type="checkbox"/> Veris <input type="checkbox"/> Others