



# Xi 400 T010

Spot finder IR camera  
for fever screening applications

when temperature matters

# optris Xi 400 T010

## TECHNICAL DATA

### Compact spot finder IR camera for fever screening applications



### Features:

- Industrial imager with 382 x 288 pixels for exact temperature measurement of -20 °C to 100 °C
- Small sized rugged camera with motorized focus
- 80 Hz frame rate for monitoring of fast thermal processes
- Extensive ready-to-use package for an attractive price – including versatile image processing software, connection cables and calibration certificate



### Technical Specifications

Optical resolution	382 x 288 pixels
Detector	FPA, uncooled (17 µm pitch)
Spectral range	8 – 14 µm
Temperature range	-20 ... 100 °C
Frame rate	80 Hz / 27 Hz
Optics (FOV)	18° x 14° (f = 20) 29° x 22° (f = 12.7) 53° x 38° (f = 7.7) 80° x 54° (f = 5.7)
Focus	Manual motor focus
Optical resolution (D:S)	390:1 (18° optics)
Thermal sensitivity (NETD)	80 mK
Accuracy	±2 °C
PC interface	USB 2.0 / optional USB to GigE (PoE) conversion
Process interface (PIF), standard	0–10 V input, digital input (max. 24 V), 0–10 V output
Cable length (USB)	1 m (standard), 3 m, 5 m, 10 m, 20 m
Ambient temperature	0 °C ... 50 °C
Enclosure (size / rating)	Ø 36 mm x 100 mm (M30x1 thread) / IP 67 (NEMA 4)
Weight (without mounting bracket)	216 - 220 g, depending on lens
Shock <sup>1)</sup> / vibration <sup>1)</sup>	IEC 60068-2-27 (25G and 50G) / IEC 60068-2-6 (sinus shaped), IEC 60068-2-64 (broadband noise)
Power supply	via USB
Scope of supply	<ul style="list-style-type: none"><li>• Process imager Xi</li><li>• USB cable (1 m)</li><li>• Standard PIF cable (1 m) incl. terminal block</li><li>• Mounting bracket with tripod thread, mounting nut</li><li>• Software package optris PIX Connect</li><li>• Certificate of calibration (reference temperature: 35 °C)</li></ul>

<sup>1)</sup> For more details see operator's manual



Xi 400 T010 and PC with software PIX Connect