

**DOW CORNING CORPORATION  
Material Safety Data Sheet****DOW CORNING(R) 44 HIGH TEMP BEARING GREASE, LIGHT****1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY**

Dow Corning Corporation  
South Saginaw Road  
Midland, Midland 48686

**24 Hour Emergency Telephone: (517) 496-5900**  
Customer Service: (517) 496-6000  
Product Disposal Information: (517) 496-6315  
CHEMTREC: (800) 424-9300

MSDS No.: 02723301

Revision Date: 2000/02/07

Generic Description: Silicone grease.  
Physical Form: Grease  
Color: Red  
Odor: Slight odor  
NFPA Profile: Health 1 Flammability 1 Instability/Reactivity 0

Note: NFPA = National Fire Protection Association

**2. OSHA HAZARDOUS COMPONENTS**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
10448-09-6	<0.1	Phenylheptamethyl cyclotetrasiloxane
33204-76-1	<0.1	2,6-cis-Diphenylhexamethyl cyclotetrasiloxane

The above components are hazardous as defined in 29 CFR 1910.1200.

**3. EFFECTS OF OVEREXPOSURE**Acute Effects

Eye: Direct contact may cause temporary redness and discomfort.  
Skin: No significant irritation expected from a single short-term exposure.  
Inhalation: No significant effects expected from a single short-term exposure.  
Oral: Low ingestion hazard in normal use.

Prolonged/Repeated Exposure Effects

Skin: Repeated or prolonged exposure may cause irritation.  
Inhalation: No known applicable information.  
Oral: Repeated ingestion or swallowing large amounts may injure internally.

Signs and Symptoms of Overexposure

**DOW CORNING(R) 44 HIGH TEMP BEARING GREASE, LIGHT**

No known applicable information.

Medical Conditions Aggravated by Exposure

No known applicable information.

The above listed potential effects of overexposure are based on actual data, results of studies performed upon similar compositions, component data and/or expert review of the product. Please refer to Section 11 for the detailed toxicology information.

**4. FIRST AID MEASURES**

Eye:	Immediately flush with water.
Skin:	No first aid should be needed.
Inhalation:	No first aid should be needed.
Oral:	Get medical attention.
Comments:	Treat according to person's condition and specifics of exposure.

**5. FIRE FIGHTING MEASURES**

Flash Point:	> 214.0 °F / > 101.1 °C Closed Cup
Autoignition Temperature:	Not determined.
Flammability Limits in Air:	Not determined.
Extinguishing Media:	Water spray. Carbon dioxide (CO <sub>2</sub> ). Dry chemical. Foam. Water can be used to cool fire exposed containers.
Fire Fighting Measures:	Self-contained breathing apparatus and protective clothing should be worn in fighting large fires involving chemicals.
Unusual Fire Hazards:	None.

Hazardous Decomposition Products

Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products: Silicon dioxide. Carbon oxides and traces of incompletely burned carbon compounds. Metal oxides. Formaldehyde.

**6. ACCIDENTAL RELEASE MEASURES**

**DOW CORNING CORPORATION  
Material Safety Data Sheet****DOW CORNING(R) 44 HIGH TEMP BEARING GREASE, LIGHT**

Containment/Clean up: Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements. Clean up remaining materials from spill with suitable absorbant. Clean area as appropriate since some silicone materials, even in small quantities, may present a slip hazard. Final cleaning may require use of steam, solvents or detergents. Observe all personal protection equipment recommendations described in Sections 5 and 8. Local, state, and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable.

Note: See section 8 for Personal Protective Equipment for Spills. Call Dow Corning Corporation, (517) 496-5900, if additional information is required.

**7. HANDLING AND STORAGE**

Use with adequate ventilation. Traces of benzene (carcinogen) may form if heated in air above 300 F (149 C). Provide ventilation to control vapor exposure within inhalation guidelines when handling at elevated temperatures. Review the OSHA benzene regulation for detailed information on safe handling requirements. Use at high temperatures may evolve or generate phenylheptamethylcyclotetrasiloxane, 2,6-cis-diphenylhexamethylcyclotetrasiloxane. Provide adequate ventilation to control within exposure guidelines. Personnel should wear organic vapor respirators until workplace exposure levels have been determined. Do not take internally. Avoid eye contact.

Use reasonable care and store away from oxidizing materials.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION****Component Exposure Limits**

<u>CAS Number</u>	<u>Component Name</u>	<u>Exposure Limits</u>
10448-09-6	Phenylheptamethyl cyclotetrasiloxane	Dow Corning guide: TWA-skin: 1.8 ppb, Wipe test guideline: 77 microgms/100 cm <sup>2</sup> .
33204-76-1	2,6-cis-Diphenylhexamethyl cyclotetrasiloxane	Dow Corning guide: TWA-skin: 0.4 ppb as vapor, 0.7 microgms/m <sup>3</sup> as aerosol, Wipe test guideline: 7 microgms/100 cm <sup>2</sup> .

**Engineering Controls**

Local Ventilation: None should be needed.  
General Ventilation: Recommended.

**Personal Protective Equipment for Routine Handling**

Eyes: Use proper protection - safety glasses as a minimum.  
Skin: Washing at mealtime and end of shift is adequate.  
Suitable Gloves: No special protection needed.

**DOW CORNING(R) 44 HIGH TEMP BEARING GREASE, LIGHT**

Inhalation: No respiratory protection should be needed.

Suitable Respirator: None should be needed.

**Personal Protective Equipment for Spills**

Eyes: Use proper protection - safety glasses as a minimum.

Skin: Washing at mealtime and end of shift is adequate.

Inhalation/Suitable Respirator: No respiratory protection should be needed.

Precautionary Measures: Do not take internally. Avoid eye contact. Use reasonable care.

Comments: Traces of benzene (carcinogen) may form if heated in air above 300 F (149 C). Provide ventilation to control vapor exposure within inhalation guidelines when handling at elevated temperatures. Review the OSHA benzene regulation for detailed information on safe handling requirements. Use at high temperatures may evolve or generate phenylheptamethylcyclotetrasiloxane, 2,6-cis-diphenylhexamethylcyclotetrasiloxane. Provide adequate ventilation to control within exposure guidelines. Personnel should wear organic vapor respirators until workplace exposure levels have been determined.

Note: These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Physical Form: Grease  
Color: Red  
Odor: Slight odor  
Specific Gravity @ 25°C: 1.1  
Viscosity: Not applicable.  
Freezing/Melting Point: Not determined.  
Boiling Point: Not determined.  
Vapor Pressure @ 25°C: Not determined.  
Vapor Density: Not determined.  
Solubility in Water: Not determined.  
pH: Not determined.  
Volatile Content: Not determined.

Note: The above information is not intended for use in preparing product specifications. Contact Dow Corning before writing specifications.

**10. STABILITY AND REACTIVITY**

Chemical Stability: Stable.

Hazardous Polymerization: Hazardous polymerization will not occur.

Conditions to Avoid: None.

**DOW CORNING(R) 44 HIGH TEMP BEARING GREASE, LIGHT**

Materials to Avoid: Oxidizing material can cause a reaction.

**11. TOXICOLOGICAL INFORMATION**

**Acute Toxicology Data for Product**

Complete information is not yet available.

**Component Toxicology Information**

This compound may contain low levels of phenylheptamethylcyclotetrasiloxane and 2,6-cis-diphenylhexamethylcyclotetrasiloxane which are estrogen-like chemicals. Estrogens are hormone substances which affect the reproductive system.

**Special Hazard Information on Components**

No known applicable information.

**12. ECOLOGICAL INFORMATION**

**Environmental Fate and Distribution**

No specific information is available.

**Environmental Effects**

No specific information is available.

**Fate and Effects in Waste Water Treatment Plants**

No specific information is available.

Ecotoxicity Classification Criteria

Hazard Parameters (LC50 or EC50)	High	Medium	Low
Acute Aquatic Toxicity (mg/L)	<=1	>1 and <=100	>100
Acute Terrestrial Toxicity	<=100	>100 and <= 2000	>2000

This table is adapted from "Environmental Toxicology and Risk Assessment", ASTM STP 1179, p.34, 1993.

This table can be used to classify the ecotoxicity of this product when ecotoxicity data is listed above. Please read the other information presented in the section concerning the overall ecological safety of this material.

**13. DISPOSAL CONSIDERATIONS**

**RCRA Hazard Class (40 CFR 261)**

When a decision is made to discard this material, as received, is it classified as a hazardous waste? No

State or local laws may impose additional regulatory requirements regarding disposal.

**DOW CORNING(R) 44 HIGH TEMP BEARING GREASE, LIGHT**

Call Dow Corning Corporate Environmental Management, (517) 496-6315, if additional information is required.

**14. TRANSPORT INFORMATION****DOT Road Shipment Information (49 CFR 172.101)**

Not subject to DOT.

**Ocean Shipment (IMDG)**

Not subject to IMDG code.

**Air Shipment (ICAO)**

Not subject to ICAO regulations.

Call Dow Corning Transportation, (517) 496-8577, if additional information is required.

**15. REGULATORY INFORMATION**

Contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.

TSCA Status: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

**EPA SARA Title III Chemical Listings****Section 302 Extremely Hazardous Substances:**

None.

**Section 304 CERCLA Hazardous Substances:**

None.

**Section 312 Hazard Class:**

Acute: No  
Chronic: Yes  
Fire: No  
Pressure: No  
Reactive: No

**Section 313 Toxic Chemicals:**

None present or none present in regulated quantities.

**Supplemental State Compliance Information****California**

Warning: This product contains the following chemical(s) listed by the State of California under the Safe Drinking

**DOW CORNING(R) 44 HIGH TEMP BEARING GREASE, LIGHT**

Water and Toxic Enforcement Act of 1986 (Proposition 65) as being known to cause cancer, birth defects or other reproductive harm.

None known.

**Massachusetts**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
4485-12-5	15.0 - 40.0	Lithium

**New Jersey**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
63148-52-7	> 60.0	Dimethyl, phenylmethyl siloxane, trimethyl-terminated
4485-12-5	15.0 - 40.0	Lithium

**Pennsylvania**

<u>CAS Number</u>	<u>Wt %</u>	<u>Component Name</u>
63148-52-7	> 60.0	Dimethyl, phenylmethyl siloxane, trimethyl-terminated
4485-12-5	15.0 - 40.0	Lithium

**16. OTHER INFORMATION**

Prepared by: Dow Corning Corporation

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is hereby made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.

(R) indicates Registered Trademark