

# Model 991R Universal Process Controller

## System Basics

- Menu Driven Graphic Controls
- Single Thermal Mass Flow Controller Channel
- Measurement Accuracy to 0.05%
- Instrument Keypad & LWAN Remote Operation
- Input Measurements - Digital, Current, Volts
- Output Controls - Relay, Current, Volts

## Display & Indicators

- Large Graphic 8x20 High Contrast Backlit Display
- Backlight Intensity Control
- Process Measurement and Alarm Status
- Audio and Visual Alarm Indicators

## Process Control Capability

- Batch Quantity Deliveries
- Dosing and Proportional Mixing

## Information Reporting

- Onboard Data Logging (optional)
- Real-Time Clock-Calendar (optional)
- Programmable Report Selection with Auto-Routing
- Programmable Clock or Alarm Instigated Reports

## Communications

- Built-in RS232 Serial Communication Port
- Multiple Unit Networked Operation
- Serial Data Packet Error Controlled
- Multiple Network Access Addresses
- Remote Serial Computer Control

## Alarm Services

- Dual Independent Input Quantity Alarms
- Operation and Maintenance Service Time
- Rate-Value High, Low, Inclusive, Exclusive & Detection

## Special Functions

- Keypad Security
- User Programmable Measure Units
- Selectable Quantity-Rate Time Base
- Universal Independent Input-Output Scaling

## Zero-Tare Capabilities

- Zero Any One or All Measured Values
- Rate-Value Offset Tare

## Diagnostic Tests

- Total Self Auto-Diagnostics on Every Power-Up

## Mounting Accessories

- Panel Hardware
- Table Top Hardware
- Rack Hardware

## Compliances

- CE Class B, RoHS, REACH, FCC 15 Class B, FCC Part 68, UL61010-1



## The Overview

Functionally and operationally identical to the Model 990X, the Florite Model 991R is an innovative, technically superior, high quality and reliable microcomputer-based controller suitable for any commercial or industrial applications. Unlike standard fixed instrument platforms, any standard sensor signal can be quickly connected directly to the Model 991R allowing the user to select from a vast number of sensor and control products, decreasing the total system cost.

## Installation and Operation

The instrument set-up and operation is performed via the keypad or using the standard RS-232 serial communication port provided with every Model 991R. The user simply configures the various programmable values required to achieve the required application performance, the Model 991R does the rest of the computing work.

## Onboard Data Logging

The onboard data logger acquires date-time stamped measurement records based on the data logger's selectable rates of seconds, minutes, hours, days, weeks, or months. The data records may be exported directly into common spreadsheet or database programs such as Microsoft™ Excel™ and Access™ for data interpretation, trending, or long-term storage.

## Communications

The instruments communication capabilities provide for sending process information, programming commands, support information, reporting and alarm signaling via its RS-232 serial communication port.

## Information Reports and Alarms

Information reports are a configurable feature that utilizes the instruments internal date-time clock. Independent channel alarms can be set for quantities, scalar values, process rates, process input measurements, and maintenance service time. Any of the independent alarms may be set to activate the audio-visual indicators and set to produce analog or relay output signals.

## Operator Controls

The Model 991R features a high contrast backlit graphic display enabling a user to view up to five control screens and adjust any of the programmable values as the process is occurring. The display, in conjunction with the audio-visual indicators provide quick and easy process status information and alarm indications.

## Diagnostics

Total self auto-diagnostic tests upon every power-up support easy installation and ensure a long and trouble-free operating life.

# Model 991R Technical Specifications

|                              |   |                       |  |
|------------------------------|---|-----------------------|--|
| <b>Control Functions</b>     | Monitor, Batch, Manual  | <b>Process Rate</b>   | 0.00±9,999.99 unit/time-base                             |
| <b>Measure Type</b>          | Rate-Total, Scalar, Pressure  | <b>Totalize Range</b> | 0-9,999.99 units   |
| <b>Process Input</b>         | Digital, Current, Volt  | <b>Process Output</b> | Current, Compensated Voltage, Relay                      |
| <b>Programmable Values</b>   |   |                       |  |
| Port Select                  | Off, Input, Output  | Rate Time Base        | scalar (none), sec, min, hrs, day                        |
| Rate Set-Point               | 0.00±9,999.99 units   | Batch Set-Point       | 0.00±9,999.99 units                                      |
| Blend Set-Point              | 0.00±9,999.99%  |                       |  |
| Rate-Value Filter            | 1.0-20 sec 10%-90%  |                       |  |
| Input Signal Interpolate     | Lo-Hi Value=0-10.000/20.000<br>Lo-Hi units=0.00±9,999.99  | Output Interpolate    | Lo-Hi Value=0-10.000/20.000<br>Lo-Hi units=0.00±9,999.99 |
| Pulse Signal Interpolate     | 0.00±9,999.99 pulse/qty ratio   | Measure Units         | 5 Chars (a-z, 0-9, A-Z, other)                           |
| Quantity 1, 2 Alarm          | 0.00-9,999.99 units   | Rate Hi-Lo Alarm      | 0.00±9,999.99 units                                      |
| Measure Units                | 5 Chars (a-z, 0-9, A-Z, other)  | Service Time Alarm    | 0-65,535 hrs   |
| <b>Global Functions</b>      |   |                       |  |
| WAN Addresses                | Dual 16 characters  | Answer Rings          | 0-255 (WAN option only)                                  |
| Network Address              | 0-65,535  | Serial Port Functions | Sio-Wan-Lan, Report-Log-Alarms                           |
| Date-Time Clock              | dd-mm-yy, hrs-min-sec   | Report/Log Frequency  | 0-999 sec-min-hrs-day-month                              |
| <b>Indicators</b>            |   |                       |  |
| Display                      | Graphic Backlit LCD   |                       |  |
| Keypad                       | 8 metal dome tactile - [Select-Prog] [Back] [Home-Start] [Stop] [Up] [Down] [Left] [Right-Alt]                  |                       |  |
| Audio                        | 2.0 KHz, 85 db @ 10 cm  |                       |  |
| <b>Input Interface</b>       |   |                       |  |
| Channels Isolation           | >85 dbv (nom)   |                       |  |
| Interface                    | 1x3 plug signal gnd excitation <or> DA15S option  |                       |  |
| Excitation                   | Vr (4.096V±0.01%) +5V Vpwr @ ~25mA max  |                       |  |
| Digital Pulse                | 0-24 V threshold 2.4V (typ) Zi~10K pulled to +5V<br>>20KHz ±0.001% hall, open collector 5V cmos switch contacts |                       |  |
| Analog Voltage               | 0-10.000V ±0.10% Zi~10.0K DA15S sense compensated   |                       |  |
| Analog Current               | 0-20.000 mA ±0.10% Zi=100 ohm   |                       |  |
| Analog Resistance            | 0-0.2M ohms   |                       |  |
| <b>Output Interface</b>      |   |                       |  |
| Interface                    | 1x3 plug signal gnd aux-signal <or> DA15S option  |                       |  |
| Analog Voltage               | 0-10.000V ±0.10% Zo<0.25 ohm DA15S option sense compensated   |                       |  |
| Analog Current               | 0-20.000mA ±0.10% Zo~2M sourcing  |                       |  |
| Relay Rating                 | Form C 28 VDC-vac 1.0A Isolated 1KV   |                       |  |
| Aux Signal                   | -4.0V to +8V @ +/- 4.0mA  |                       |  |
| Power Control                | 2.0 Amps Max.   |                       |  |
| <b>Serial Ports</b>          |   |                       |  |
| Sio                          | EIA-TIA232D fdx D9S   |                       |  |
| Wan                          | USOC RJ-11 tip-ring FCC Subpart H fdx WAN option  |                       |  |
| Lan                          | EIA-TIA485 multidrop master-slave option <or> 10-100 Ethernet option  |                       |  |
| <b>Value Memory</b>          |   |                       |  |
|                              | Nvram 8Kx8 non-volatile parallel  |                       |  |
|                              | Eerom 512x8 non-volatile 100 yr retention, Eerom 256Kx8 non-volatile serial log option                          |                       |  |
|                              | Static ram 1Kx8 parallel, Static ram 32x8 serial battery backed   |                       |  |
| <b>Power Required</b>        |   |                       |  |
| Volts-Power                  | 12-24 VDC 2.0w (without options)  |                       |  |
| Jack Unipolar                | 2.1<or>2.5mm 2A<or>5A center pos UL/CSA   |                       |  |
| Plug Bipolar                 | DE9P 5A rated UL/CSA  |                       |  |
| Battery                      | Lithium 3.0V 12mm 35 mA-hr 9 yr operate date-time clock option  |                       |  |
| <b>Operating Environment</b> |   |                       |  |
| Operation                    | 0-38°C 0-95% RH non-condensing  |                       |  |
| Ship-Storage                 | -20° to +85°C 0-95% RH non-condensing   |                       |  |
| Warm Up                      | 3 sec typical to rated accuracy   |                       |  |
| <b>Self Diagnostics</b>      |   |                       |  |
|                              | Memory validities, installation, communication local-remote   |                       |  |
| <b>Enclosure</b>             |   |                       |  |
| Mounting                     | ABS plastic NEMA 4X front panel   |                       |  |
| Panel Cut-Out                | Frame, panel, desk-top, rack<br>Rectangular 4.4 x 4.3   |                       |  |
| <b>Weight</b>                |   |                       |  |
|                              | 350gm (without options)   |                       |  |
| <b>Compliances</b>           |   |                       |  |
|                              | CE Class B, RoHS, REACH, FCC 15 Class B, FCC Part 68, UL61010-1   |                       |  |

Specifications are subject to change at any time without notice.

For more information regarding the Model 991R please contact Florite International, Inc.

Domestic: 866-4-Florite (435-6748)  
International: 818-994-3454  
[www.florite.com](http://www.florite.com)

D10171-061617