



Welding adapters EN10357 series C (ASME BPE)

ADAPT EN10357-C DN80



EC 1935/2004 FCM FDA

Application

| | |
|-----------------|--|
| Design | for volumetric flow meters SMF |
| Application | food and beverage industry; hygienic systems |
| Pressure rating | 25 bar 2.5 MPa |

Tests / approvals

| | |
|------------------------------|---|
| Pressure Equipment Directive | A possible classification to PED depends on the application and has to be carried out by the user / operator. |
| Safety instructions | The compatibility between medium and product material has to be checked in all applications. |

E40625



Welding adapters EN10357 series C (ASME BPE)

ADAPT EN10357-C DN80

| Mechanical data | |
|---|---|
| Weight | [g] |
| Materials (wetted parts) | stainless steel (316L/1.4404) |
| Nominal diameter | DN80 (3") |
| Sensor connection | ifm-specific device flange |
| Process connection | welding adapter EN10357 series C (ASME BPE) |
| Process connection suitable for pipe standard | (DIN EN 10357 series C); (DIN EN 10357 series D); (DIN 11866 series C); (BS 4825 Part 1); (ISO 2037) |
| Surface characteristics Ra/Rz of the wetted parts | Ra < 0.4 µm |
| Accessories | |
| Items supplied | screws 12 |
| Remarks | |
| Pack quantity | 2 pcs. |